



FDV – Management, operation, and maintenance

Herregård Exclusive Dør og Vindu



Herregård Exclusive Dør og Vindu is a non-sticky, durable, and opaque oil-based paint for exterior use. It adheres exceptionally well and maintains its gloss and color over time. Contains a film-preserving agent that prevents the growth of mold and algae. Herregård Exclusive Dør og Vindu is suitable for planed wood such as windows, doors, fences, garage doors, trim, garden furniture, and similar applications. It can be used on exterior new or old wood, as well as stained, painted, or pressure-treated wood. It can also be used as a topcoat on primed metal and plastic commonly found on buildings, such as gutters, flashings, and similar surfaces.

Revised

18.08.2025

Application Instructions

Substrate:

The surface must be dry and frost-free, with a minimum temperature of 0°C.

Application Methods:

Brush, roller, or spray. Spraying should be performed by professionals.

Thinner:

White Spirit; thinning is normally not required.

Storage:

Store and transport upright, in a dry and frost-free environment, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/e): 300 g/l (2010). The product contains <300 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Husvask is recommended. For cleaning before repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed before 3-4 weeks.

Interval:

The paint film naturally deteriorates due to weather exposure, which will vary depending on local conditions. Repainting should therefore be done as needed, when the film appears dull and worn. Walls exposed to the elements typically require more frequent repainting than other parts of the building.

Waste Disposal

Liquid paint must not be poured into drains or released into the environment, but must be delivered to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste. Empty metal cans must be delivered to a recycling station.

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

Surface/Material Information**Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this data sheet is based on laboratory tests and practical experience. Our products are considered semi-finished goods, and as conditions of use are often beyond our control, we can only guarantee the product's quality. Products are delivered under our general terms for sale, delivery, and service unless otherwise agreed in writing. We reserve the right to make minor product changes and amend the specified data without prior notice. This data sheet replaces earlier versions and is automatically invalid five years after the publication date.

Contact Information**Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt, Norway

Phone: +47 712 91 700

Email: office@gjoco.no

