

# Product Data Sheet

## Gjøco AquaShield Siloksan Murfiller



Gjøco AquaShield Siloksan Murfiller is a filler that provides structure based on silicone emulsion. For outdoor use on all types of plaster, foundations and concrete. Particularly suitable for older sanded surfaces with cracks, flaking or other irregularities. Use as an intermediate coat on primed or previously painted mineral substrates when system painting with AquaShield Siloksan Murprimer and AquaShield Siloksan Murmaling.

Revised

12.01.2026

Symbols



Technical data	Type:	Water-thinned diffusion-open masonry paint based on silicone emulsion
Color:	White, base A and C, as well as light grey, medium grey and deep grey	
Liter weight:	1.6 kg/l	
Dry matter:	Approx. 60% by volume	
Method of application:	Brush	
Thinner/Cleaner:	Water, washed with soap and water. The product should not be thinned.	
Recommended consumption:	3-4 m2/litre, depending on the substrate	
Drying time (23 °C, 50% R.H.):	Depends on temperature, humidity, wind and film thickness	
Dust dry:	4 hours	
Repainting interval, minimum:	12 hours	
Minimum application temperature:	+2 °C	

### Pre-treatment

The substrate must be clean, firm and dry. All old loose paint, lime, loose plaster and dust must be removed with a wire brush/scraper. Clean with Gjøco Kraft to remove grease and contaminants, rinse with clean water. The surfaces must be dry before further treatment and plaster repairs must harden in min. 4 weeks before overpainting. All technical deficiencies must be rectified before further processing. It is important that the substrate is firm to ensure good adhesion. All bare untreated plaster/concrete must be primed with AquaShield Siloksan Murprimer.

### Method of use

Stir the paint well before use. The product is applied with a brush and must be cross-brushed for the best possible structure levelling and scratch superstructure. For filling unevenness and cracks up to 5 mm thick. To be painted over with AquaShield Siloksan Murmaling. AquaShield Siloksan products should not be

used on horizontal surfaces such as floors etc., which are exposed to high water loads. Do not paint in direct sunlight or if there is a risk of rain or dew during the first few hours after the end of the work.

---

<b>Storage</b>	Seal the lid tightly when storing paint to prevent spillage and drying out. The product must be transported and stored upright, dry and frost-free.
----------------	---

<b>Waste management</b>	Liquid brick fillers must not be emptied into sewage drains or in nature, but delivered to an approved reception centre for hazardous waste. Empty, clean and dry plastic packaging without a handle, can is delivered as plastic waste.
-------------------------	--



---

<b>Other information</b>	Stir well. The product must not be exposed to frost. Packaging sizes: 3 and 10 litres.
--------------------------	---

<b>Security</b>	See separate safety data sheet. Read the information on the packaging. EU limit value for the product (cat. A/c): 40 g/l. The product contains a maximum of 30 g/l VOC.
-----------------	--

---

The information in this datasheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the result depends on surface preparation, temperature, application, substrate type, and other factors.

---

<b>Contact information</b>	<b>Gjøco AS</b> Ørvegen 1160, 6639 Torvikbukt Phone: +47 712 91 700 E-mail: <a href="mailto:office@gjoco.no">office@gjoco.no</a>
----------------------------	---

