



FDV – Management, operation, and maintenance

Gjøco AquaShield Siloksan Mурмaling



Gjøco AquaShield Siloksan Mурмaling is a matte, vapor-permeable silicone emulsion paint for exterior use on mineral substrates. Gjøco AquaShield Siloksan Mурмaling contains lightfast and mineral pigments that provide good weather resistance. The paint is formulated with a film-protective, anti-fungal agent. Gjøco AquaShield Siloksan Mурмaling is particularly suitable for exterior use on all types of masonry, foundation walls, render, and concrete. It is used as a topcoat on primed or previously painted mineral substrates when applying a system with Gjøco AquaShield Siloksan Murprimer and Gjøco AquaShield Siloksan Murfiller.

Revised

14.01.2026

Application Instructions	Substrate:	The substrate must be clean and dry, with a minimum temperature of +2 °C.
	Application Methods:	Brush, roller, or spray..
	Thinner:	Water; thinning is normally not required.
	Storage:	Store and transport upright, in a dry and frost-free environment, out of reach of children.
	Transport:	Not classified as dangerous goods under current regulations.
	Indoor Environment/Emission:	The product is intended for outdoor use.
	Product Data and Safety Data	A product data sheet and safety data sheet (SDS) are available for this product. Visit www.gjoco.no . VOC: EU limit for this product (category A/c): 40 g/L (2010). The product contains <30 g/L VOC.
Maintenance	Cleaning:	For annual cleaning, Gjøco Husvask is recommended. For cleaning prior to repainting, Gjøco Kraftvask is recommended. Follow the product instructions.
	Interval:	The paint film naturally degrades due to weather exposure and will vary depending on local conditions. Repainting should therefore be carried out as needed, and when the film appears matte and worn. Weather-exposed walls are more exposed to the elements and normally require more frequent repainting than the rest of the building.

Liquid paint must not be discharged into drains or into the natural environment, but must be delivered to an approved hazardous waste collection facility. Empty, clean, and dry plastic packaging without handles may be disposed of as plastic waste.


Waste Disposal

Repairs/Damage Repairs and damage should be carried out using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work must be carried out so that it does not differ from earlier treatments. For repainting or when changing color, it is recommended to use the same product as before. Contact your dealer or a painting contractor.

Surface/Material Information:
Painted in color:
Color name:
NCS:
Batch number:
Work performed by:
Date:
Signature:

The information in this datasheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the results depend on surface preparation, temperature, application, substrate type, and other factors.

Contact Information
Gjøco AS

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

