



## FDV – Management, operation, and maintenance

# Gjøco AquaShield Siloksan Murprimer



Gjøco AquaShield Siloksan Murprimer is an unpigmented silicone emulsion primer for exterior use on mineral substrates such as masonry, foundation walls, render, and concrete. It is used as a hydrophobizing primer on chalking and highly absorbent mineral substrates when applying a system with AquaShield Siloksan Murfiller and AquaShield Siloksan Mурмaling.

Revised	15.01.2026
<b>Application Instructions</b>	
<b>Substrate:</b>	The substrate must be clean and dry, with a minimum temperature of +5 °C.
<b>Application Methods:</b>	Brush.
<b>Thinner:</b>	Water; thinning is normally not required.
<b>Storage:</b>	Store and transport upright, in a dry and frost-free environment, out of reach of children.
<b>Transport:</b>	Not classified as dangerous goods under current regulations.
<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Product Data and Safety Data</b>	
	A product data sheet and safety data sheet (SDS) are available for this product. Visit <a href="http://www.gjoco.no">www.gjoco.no</a> . <b>VOC:</b> EU limit for this product (category A/h): 0 g/L (2010). The product contains <30 g/L VOC.
<b>Maintenance</b>	Gjøco AquaShield Siloksan Murprimer is intended to be overpainted within a short time. Therefore, washing/maintenance is normally not required.
<b>Waste Disposal</b>	Liquid primer must not be discharged into drains or into the natural environment, but must be delivered to an approved hazardous waste collection facility. Empty, clean, and dry plastic packaging may be disposed of as plastic waste.

**Repairs/Damage**

Repairs and damage should be carried out using the same type of product. If other products are used, it must be documented that they are of the same type as previously applied. When repairing damage, the work must be carried out so that it does not differ from earlier treatments. For repainting or when changing color, it is recommended to use the same product as before. Contact your dealer or a painting contractor.

**Surface/Material Information:****Painted in color:****Color name:****NCS:****Batch number:****Work performed by:****Date:****Signature:**

The information in this datasheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. The products are supplied in accordance with our general terms of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the results depend on surface preparation, temperature, application, substrate type, and other factors.

**Contact Information****Gjøco AS**

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: [office@gjoco.no](mailto:office@gjoco.no)