

# FDV – Management, Operation and Maintenance

## Gjøco Proff Mester Tre og Panel 15



Gjøco Proff Mester Tre og Panel 15 is a low-odor, silk-matte, washable waterborne oil paint for indoor use on wood. It provides a durable and smooth finish and is suitable for panels, window frames, trim, doors, furniture, MDF, and interior fittings.

Revised

24.03.2026

<b>Usage Instructions</b>	<b>Surface Preparation:</b>	The surface must be clean and dry, with a minimum temperature of +10 °C. Best results are achieved when applied at room temperature (above +20 °C).
	<b>Application Method:</b>	Brush, roller, or spray. Spraying should be performed by professionals.
	<b>Thinner:</b>	Water; thinning is usually not necessary.
	<b>Storage:</b>	Store and transport upright, dry, frost-free, and out of reach of children..
	<b>Transport:</b>	Not classified as hazardous goods under applicable regulations.
	<b>Indoor Environment/Emissions</b>	The product emits low emissions.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS) are available at <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC Content: EU limit for the product (cat. A/d): 130 g/l (2010). This product contains <75 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For cleaning before repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Gulv- og panelrens or Gjøco Interiørvask. Follow the instructions on the product. Newly painted surfaces should not be washed until 4 weeks after painting. Use microfiber cloths with clean water or mild soapy water. The water temperature should not exceed +40 °C, and the pH should not exceed 9. Cleaning agents containing abrasives may damage the surface. Clean in a way that avoids streaks, and perform cleaning as needed. The paint film will wear faster under heavy cleaning.

---

**Intervals:** The paint film is affected by mechanical stress and wears according to the level of use. Maintenance intervals will therefore vary depending on need.

---

**Waste Management** Liquid paint and wash water must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.



---

**Repairs/Damage** Repairs and damage should be repaired using the same type of product. If a different product is used, it must be documented that it is compatible with the previously applied product. Repairs should be carried out so that they do not differ from previous treatments. When repainting or changing color, it is recommended to use the same product as before. Contact your dealer or painting company for guidance.

---

**Environmental Labeling** Gjøco Proff Mester Tre og Panel 15 is approved by the Nordic Ecolabel (Swan) and meets its environmental requirements.



BREEAM-NOR v6.1:

-HEA02: The product complies with VOC content according to EU Directive 2004/42/EC and emission requirements tested according to the ISO 16000 and ISO 11890 series.

-MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List, or the Norwegian A20 list. See the product's safety data sheet for more information.

---

**Treated Surface/Type of Substrate:**

.....

**Painted in Color:**

**Color Name:**

.....

**NCS:**

.....

**Batch Number:**

.....

**Painting Performed By:**

.....

**Date:**

.....

**Signature:**

.....

---

---

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbukt  
Phone: +47 712 91 700  
Email: [office@gjoco.no](mailto:office@gjoco.no)

