

FDV – Management, Operation and Maintenance

Gjøco Proff Mester Vegg og Tak 05



Gjøco Proff Mester Vegg og Tak 05 is a waterborne, matte, durable, and washable acrylic paint for indoor use. The paint is stain-resistant, does not leave marks after cleaning, and provides excellent coverage in two coats. It is suitable for walls and ceilings on substrates such as paintable wallpaper, building boards, MDF, glass fiber fabric, textured fabric, wallpaper, plaster, masonry, concrete, and skim-coated surfaces.

Revised

25.03.2026

Usage Instructions	Surface:	The surface must be clean and dry, with a minimum temperature of +10 °C.
	Application Method:	Apply by brush, roller, or spray. Spraying should be carried out by professionals. Using a roller with an extension pole is recommended, as it helps to avoid streaks.
	Thinner:	Water, thinning is usually not necessary.
	Storage:	Store and transport upright, dry, frost-free, and out of reach of children..
	Transport:	Not classified as hazardous goods under applicable regulations.
	Indoor Environment/Emissions	The product emits low emissions.
Technical and Safety Data	A technical data sheet and safety data sheet (SDS) are available at www.gjoco.no . VOC Content: EU limit for the product (cat. A/a): 30 g/l (2010). This product contains <1 g/l VOC.	
Maintenance	Cleaning:	For cleaning prior to repainting, it is recommended to use an alkaline cleaning agent such as Gjøco Interiørvask or Gjøco Gulv- og panelrens. Follow the instructions on the product. Newly painted surfaces should not be washed until after 4 weeks. Use microfiber cloths with clean water or mild soapy water. The temperature of the wash water should not exceed +40 °C, and the pH should not exceed 9. Cleaning agents containing abrasives may damage the surface. Clean in a way that avoids streaks, and perform

cleaning as needed. The paint film will wear faster under heavy cleaning.

Intervals:

The paint film is affected by mechanical wear and will deteriorate depending on the level of use. Maintenance intervals will therefore vary as needed.

Waste Management

Liquid paint and wash water must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.



Repairs/Damage

Repairs and damage should be carried out using the same type of product. If a different product is used, it must be documented that it is compatible with the previously applied product. Repairs should be performed in a way that does not differ from earlier treatments. When repainting or changing color, it is recommended to use the same product as before. Contact your dealer or painting contractor for advice.

Environmental Labeling

Gjøco Proff Mester Vegg og Tak 05 is approved by Miljømerking Norge and meets the requirements of the Nordic Swan Ecolabel.



BREEAM-NOR v6.1

-HEA02: The product complies with VOC content according to EU Directive 2004/42/EC and emission requirements tested in accordance with the ISO 16000 and ISO 11890 series.

-MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List, or the Norwegian A20 list. See the product's safety data sheet for more information.

Approved according to Byggvarubedømmingen's assessment criteria.

Treated Surface/Type of Substrate:

Painted in Color:

Color Name:

NCS:

Batch Number:

Painting Performed By:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS

Ørvegen 1160, 6639 Torvikbukt

Phone: +47 712 91 700

Email: office@gjoco.no

