

Product Data Sheet

Gjøco Proff Mester Vegg og Tak 05



Gjøco Proff Mester Vegg og Tak 05 is a waterborne, matte, durable, and washable acrylic paint for indoor use. The paint is stain-resistant, does not leave marks after cleaning, and provides excellent coverage in two coats. It is suitable for walls and ceilings on substrates such as paintable wallpaper, building boards, MDF, glass fiber fabric, textured fabric, wallpaper, plaster, masonry, concrete, and skim-coated surfaces.

Revised 24.03.2026

Symbols



Technical data

Type:	Waterborne acrylic dispersion paint
Color:	White, A, B and C base, colors are mixed over Gjøcomix.
Gloss:	Matte 05
Density:	1.3 kg/l
Solid content:	Ca. 40 volum%
Application method:	Brush, roller, or spray. Spraying should be done by professionals. It is best to use a roller with an extension handle because it is easier to avoid streaks.
Thinner/ cleaning agent:	Water
Recommended spreading rate:	8 - 10 m ² /litre, depending on the substrate.
Recommended data for airless spray:	
Nozzle tip:	0.43–0.53 mm (0.017–0.021")
Spray angle degrees:	50°-80°
Pressure at nozzle:	Follow the pump manufacturer's recommendations.
	The choice of nozzle, fan angle, and pressure must be adjusted to the specific spray equipment and substrate.
Drying times (23 °C, 50 % R.H.):	
Dry to use:	1 hours
Interval between coats:	2 hours
Minimum application temperature:	+10 °C. Best results are achieved when applied at room temperature.

Pretreatment	The surface must be clean and dry. Clean with Gjøco Interiærvask or Gulv- og panelrens. Previously oil-painted surfaces, MDF boards, and hard, smooth substrates should be lightly sanded and primed with Gjøco Proff Isolér.
Directions for use	Apply evenly and generously. On absorbent and porous surfaces, 3 coats are recommended to avoid streaks. Using a roller with an extension pole is recommended, as it helps prevent streaks. For a uniform finish, it is best to roll entire lengths in the same direction across the whole wall.
Color	Use the same batch number for the same coat and surface to avoid differences in color and sheen. Different batch numbers can be mixed together before use if needed. Cans mixed on different machines and/or at different times may result in slight color variations. Be aware of this if additional paint is required for the same project later.
Storage	Close the lid tightly when storing the paint to prevent spills and drying out. The paint should be transported and stored upright, in a dry and frost-free environment.
Eco-labeling	<p>Gjøco Proff Mester Vegg og Tak 05 is approved by Miljømerking Norge and meets the requirements of the Nordic Swan Ecolabel.</p>  <p>BREEAM-NOR v6.1:</p> <ul style="list-style-type: none"> – HEA02: The product complies with VOC content requirements in accordance with EU Directive 2004/42/EC and emission requirements tested in accordance with the ISO 16000 and ISO 11890 series. – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.
Disposal of waste	<p>Liquid paint and wash water must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.</p> 
Other information	<p>The air and substrate temperature must be at least +10 °C. Painted surfaces must cure for a minimum of 4 weeks before cleaning with a mild detergent. Light marks on dark surfaces can be removed with a microfiber cloth and clean water. Stir well before use.</p> <p>Container size: 9 L.</p>
Safety	<p>See separate safety data sheet. Read the information on the packaging.</p> <p>EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains: <1 g/l VOC.</p>

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

