



FDV – Management, operation, and maintenance

Gjøco Proff MesterTre Max 30



Gjøco Proff MesterTre Max 30 is a durable and opaque wood protection paint for outdoor cladding. It contains high-quality binders and pigments that provide long-lasting protection and excellent color and gloss stability. The paint includes a film-preserving agent that prevents the growth of black mold and algae on the surface. Suitable for new, old, stained, painted, or pressure-treated wood. Gjøco Proff MesterTre Max 30 can also be used as a topcoat on primed metal and plastic, such as gutters, flashings, and similar building elements.

Revised

24.03.2026

Application Instructions

Substrate:

The surface must be clean, dry, and have a minimum temperature of +5°C.

Application Methods:

Brush, roller, or spray. Spraying should be carried out by professionals.

Thinner:

Water, thinning is usually not necessary.

Storage:

Store and transport upright, dry, and frost-free, out of reach of children.

Transport:

Not classified as dangerous goods under applicable regulations.

Indoor Environment/Emission:

The product is intended for outdoor use.

Technical and Safety Data

A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See www.gjoco.no. VOC: EU limit for the product (cat. A/d): 130 g/l (2010). The product contains <30 g/l VOC.

Maintenance

Cleaning:

For annual cleaning, Gjøco Husvask is recommended. If other cleaning agents are used, the pH should not exceed 9. For cleaning prior to repainting, Gjøco Kraftvask is recommended. Follow the instructions on the product. Newly painted wood should not be washed until 3–4 weeks after painting.

Interval:

The paint film naturally deteriorates due to weathering and will vary depending on local conditions. Repainting should therefore be done as needed, when the film appears dull and worn. Exterior walls exposed to weather typically require more frequent repainting than the rest of the building.

Waste Disposal

Liquid paint must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.



Repairs/Damage

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

Surface/Material Information

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact Information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Phone: +47 712 91 700
Email: office@gjoco.no

