



## FDV – Management, operation, and maintenance

# Gjøco Proff MesterTre Premium 50



Gjøco Proff MesterTre Premium 50 is a waterborne oil paint for outdoor cladding, designed with a surface that resists dirt accumulation and has self-cleaning properties. Its unique technology provides excellent color and gloss stability and long maintenance intervals. The paint contains a film-preserving agent that prevents the growth of black mold and algae on the surface. Suitable for new, old, stained, painted, or pressure-treated wood. Gjøco Proff MesterTre Premium 50 can also be used as a topcoat on primed metal and plastic, such as gutters, flashings, and similar building elements.

Revised

24.03.2026

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean, dry, and have a minimum temperature of 5°C.
	<b>Application Methods:</b>	Brush, roller, or spray. Spraying should be performed by professionals.
	<b>Thinner:</b>	Water, thinning is usually not necessary.
	<b>Storage:</b>	Store and transport upright, dry, and frost-free, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A technical data sheet and safety data sheet (SDS / MSDS) have been prepared for the product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit for the product (cat. A/d): 130 g/l (2010). The product contains <30 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. If other cleaning agents are used, the pH should not exceed 9. For cleaning before repainting, Gjøco Kraftvask is recommended—follow the instructions on the product. Newly painted wood should not be washed until 3–4 weeks after painting.
	<b>Interval:</b>	The paint film naturally deteriorates due to weathering and will vary depending on local conditions. Repainting should therefore be done as needed, when the film appears dull and worn. Exterior walls exposed to the elements typically require more frequent repainting than the rest of the building.

---

**Waste Disposal**

Liquid paint must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry plastic containers without handles can be disposed of as plastic waste.



---

**Repairs/Damage**

Repairs and damages should be addressed using the same product type. Documentation must prove the same product type was previously used if other products are applied. Repairs should match the existing treatment. For repainting or color changes, it is recommended to use the same product as before. Contact a retailer or painting company for assistance.

---

**Surface/Material Information**

**Painted in color:**

**Color name:**

**NCS:**

**Batch number:**

**Work performed by:**

**Date:**

**Signature:**

---

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

---

**Contact Information**

**Gjøco AS**  
Ørvegen 1160, 6639 Torvikbuk  
Phone: +47 712 91 700  
Email: office@gjoco.no

