



## FDV – Management, operation, and maintenance

### Gjøco Tyri Terrasseolje



Gjøco Tyri Terrasseolje is a specialty oil for treating pressure-treated wood used for terraces, garden furniture, screens, railings, and similar surfaces. It contains weather-resistant alkyd oils, linseed oil, and wood tar, along with effective agents against surface mold and algae. It has excellent penetration, minimizing the risk of peeling. It is recommended to use Gjøco Tyri Terrasseolje with added color pigment, as pigmentation provides increased UV protection. Gjøco Tyri Terrasseolje can also be used on royal-treated decking that is worn and in need of re-treatment.

Revised

10.04.2026

<b>Application Instructions</b>	<b>Substrate:</b>	The surface must be clean and dry, with a minimum temperature of 0 °C.
	<b>Application Methods:</b>	Pad, brush, or roller. Do not spray.
	<b>Thinner:</b>	White Spirit. The product normally does not require thinning.
	<b>Storage:</b>	Store and transport upright, in a dry and frost-free environment, out of reach of children.
	<b>Transport:</b>	Not classified as dangerous goods under applicable regulations.
	<b>Indoor Environment/Emission:</b>	The product is intended for outdoor use.
<b>Technical and Safety Data</b>	A product data sheet and safety data sheet have been prepared for this product. See <a href="http://www.gjoco.no">www.gjoco.no</a> . VOC: EU limit value for the product (cat. A/f): 700 g/l (2010). This product contains <600 g/l VOC.	
<b>Maintenance</b>	<b>Cleaning:</b>	For annual cleaning, Gjøco Husvask is recommended. Clean with Gjøco Terrasserens before re-staining. Follow the instructions on the product. Newly painted wood should not be washed until after 3–4 weeks.
	<b>Interval:</b>	The paint film naturally breaks down due to weather exposure and will vary depending on local conditions. Recoating should therefore be done as needed, when the surface becomes dull and worn. Weather-exposed walls are more exposed to the elements and typically require more frequent recoating than the rest of the building.

**Waste Disposal**

Liquid oil must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry containers should also be delivered to an approved collection point.

**Repairs/Damage**

Repairs and damage should be touched up using the same type of product. Documentation must show that the same type of product was previously used if other products are applied. Repairs should be carried out in such a way that they do not deviate from previous treatments. When repainting or changing color, it is recommended to use the same product that was used before. Contact your dealer or paint supplier for further advice.

**Eco-labeling**

BREEAM-NOR v6.1  
 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.

**Surface/Material Information**

Painted in color:

Color name:

NCS:

Batch number:

Work performed by:

Date:

Signature:

The information in this data sheet is based on laboratory tests and practical experience. Since the conditions under which the products are used are often beyond our control, we can only guarantee the quality of the product itself. Products are supplied in accordance with our general terms for sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint should be considered a semi-finished product, and the result depends on surface preparation, temperature, application, substrate type, and other factors.

**Contact Information**

**Gjøco AS**  
 Ørvegen 1160, 6639 Torvikbukt  
 Phone: +47 712 91 700  
 Email: office@gjoco.no

