

Product Data Sheet

Gjøco Tyri Terrasseolje



Gjøco Tyri Terrasseolje is a specialty oil for treating pressure-treated wood used in decks, garden furniture, screens, railings, and similar applications. It contains weather-resistant alkyd oils, linseed oil, and wood tar, and includes effective agents against surface fungi and algae. It has excellent penetration properties, which reduce the risk of peeling.

It is recommended to use Gjøco Tyri Terrasseolje with added color pigments, as pigmentation provides increased UV protection. Gjøco Tyri Terrasseolje can also be used on Royal-treated decking boards that are worn and in need of re-treatment.

Revised

19.03.2026

Symbols




Technical data

Type:	Solvent-based with high-quality alkyd, linseed oil, and wood tar
Color:	Base C and base yellow, which can be tinted to the desired color, as well as ready-made colors Brown RB-10, Black RS-25, and Grey RG-25
Viscosity:	60–70" F4
Density:	0.9 kg/l
Solids content:	Approx. 38% by volume
Application method:	Pad, brush, or roller. Must not be sprayed
Thinner / cleaning agent:	White Spirit. The product should normally not be thinned
Recommended coverage:	Approx. 6–8 m ² /litre per coat, planed wood
Drying time (23 °C, 50% R.H.):	Depends on temperature, humidity, wind conditions, and film thickness
Ready for use:	12 hours
Dust dry:	4 hours
Minimum application temperature:	0 °C. Low temperatures result in longer drying times and increased risk of dew matting, etc.

Pretreatment

The substrate must be clean and dry. New, pressure-treated wood must be dry before treatment; this may take anywhere from a few weeks to 2–3 months. Rinse and brush off any residues from the impregnation process. Clean the deck with Gjøco Terrasserens. Follow the instructions on the packaging. Allow to dry thoroughly before further treatment. The deck should be treated as soon as possible after it is clean and dry to prevent surface wear caused by weather exposure.

	<p>When treating old or previously treated wood, clean the deck with Gjøco Terrasserens Gel. Follow the instructions on the packaging. Repeat the treatment if the surface is heavily soiled. Allow to dry thoroughly before further treatment. Loose stain and oil must be removed, and grey, weathered surfaces must be wire-brushed or sanded down to fresh wood before treatment. Loose flakes and wood fibers/grey wood may prevent proper penetration and cause peeling.</p> <p>When cleaning decks made of larch and tropical wood species, follow the supplier's guidelines for the use of cleaning agents.</p>
Directions for use	<p>Gjøco Tyri Terrasseolje is applied using a pad, roller, or brush. The product can be used at temperatures down to 0°C (the surface must be dry and free from frost). Apply the decking oil along the full length of the boards, treating 2–3 boards at a time. Any excess oil that has not been absorbed into the wood should be wiped off after about one hour. Avoid application in strong sunlight, damp weather, or at low temperatures. Low temperatures and high humidity will extend the drying time. Take extra care during spring and autumn when night temperatures are low.</p> <p>The oil will penetrate differently in areas around knots and softer parts of the wood, which may result in color variation. Treatment of knots and dense hardwood species such as larch may result in reduced durability due to limited penetration into the wood.</p>
Color	<p>The decking oil is transparent, and the final color will therefore vary depending on the substrate. Keep in mind that the color becomes richer and darker with each additional coat. It is recommended to apply a test coat to ensure the desired color is achieved. Use of the oil without added tint/pigment is not recommended. Always use the same batch number for the same coat and surface to avoid color variation.</p>
Storage	<p>Close the lid tightly when storing the decking oil to prevent spills and drying out. The decking oil must be transported and stored upright, in a dry and frost-free environment.</p>
Eco-labeling	<p>BREEAM-NOR v6.1 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.</p>
Disposal of waste	<p>Liquid oil must not be disposed of in drains or released into the environment, but delivered to an approved facility for hazardous waste. Empty, clean, and dry packaging should be delivered to an approved recycling facility.</p> <p></p>
Other information	<p>Stir any oil separation thoroughly before use. It is not recommended to use the oil without added tint/pigment. Packaging sizes: 4,5 and 5 liters.</p>
Safety	<p>Refer to the separate Safety Data Sheet. Read the information on the packaging. EU limit value for this product (cat. A/f): 700 g/l (2010). This product contains: <600 g/l VOC.</p>

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

