

Product Data Sheet

Gjøco Tyri Tømmerolje



Gjøco Tyri Tømmerolje is a specialty outdoor oil for treating log buildings, wilderness cladding, stave construction, and wooden roofs. It contains linseed oil, wood tar, and turpentine, traditionally used for timber treatment. The timber oil has excellent penetration, minimizing the risk of peeling. It soaks into the wood, providing essential protection against moisture and weather exposure. It also contains effective agents against surface mold and moss. It is recommended to use Gjøco Tyri Tømmerolje with added color pigment, as the pigmentation increases UV protection.

Revised 19.03.2026

Symbols



Technical data


Type:	Tar-based specialty oil made from linseed oil and wood tar
Color:	Base C and yellow base, mixed to the desired color
Density:	Approx. 0.9 kg/l
Solids content:	Approx. 38% by volume
Application method:	Wide brush
Thinner / cleaning agent:	White Spirit. The product normally does not need thinning
Recommended coverage:	Approx. 4–6 m ² /l per coat on planed wood
Drying time (23 °C, 50% R.H.):	Depends on temperature, humidity, wind conditions, and film thickness
Recoatable:	24 hours
Touch dry:	4 hours
Minimum application temperature:	0 °C. Low temperatures result in longer drying times and increased risk of dew matting, etc.

Pretreatment

The surface must be clean and dry. New wood should be treated as soon as possible after installation. New wood that has been left untreated for more than 4 weeks should be cleaned and wire-brushed before further treatment to remove loose wood fibers. Previously oiled wood should be cleaned with Gjøco Kraftvask to remove grease and contaminants.

Directions for use

Gjøco Tyri Tømmerolje is applied with a wide brush. Apply the timber oil in an even, thin coat. The oil should penetrate the wood and should not form a surface film. All end grain, joints, and log knots must be thoroughly saturated with Gjøco Tyri Tømmerolje. Exterior walls may require more than one coat and will also need more frequent maintenance than other walls.

	The surface will wear differently depending on weather exposure, and parts of walls under a roof will not require treatment as often as more exposed areas. Uneven weathering will naturally create variations in color between different walls and sections. Reapply the surface treatment when the wood appears dry and gray. Gjøco Tyri Tømmerolje can be applied year-round, but the wood must be dry and free of frost.
Color	The timber oil is transparent, so the color will vary depending on the substrate. Keep in mind that the color becomes richer and darker with each additional coat. It is recommended to apply a test coat to ensure the desired color. Use the same batch number for the same coat and surface to avoid color variations. Gjøco Tyri Tømmerolje is available in Base C and yellow base and can be mixed into a wide range of colors.
Storage	Close the lid tightly when storing the timber oil to prevent spills and drying out. The timber oil should be transported and stored upright, in a dry and frost-free environment.
Eco-labeling	BREEAM-NOR v6.1 – MAT02: Contains no substances listed under REACH Article 59(10) – the Candidate List and the Norwegian A20 list. See also the product safety data sheet.
Disposal of waste	Liquid oil must not be poured into drains or released into the environment, but should be taken to an approved hazardous waste facility. Empty, clean, and dry containers should also be delivered to an approved collection point. 
Other information	Any oil separation should be stirred thoroughly before use. It is not recommended to use the oil without added tint/pigment. Available container sizes: 4,5 liter.
Safety	See the separate safety data sheet. Read the information on the packaging. EU limit value for this product (cat. A/e): 400 g/l (2010). This product contains: <100 g/l VOC.

The information provided in this data sheet is based on laboratory tests and practical experience. As the conditions under which the products are used are often beyond our control, we cannot guarantee anything other than the quality of the product itself. The products are supplied in accordance with our general terms and conditions of sale, delivery, and service, unless otherwise agreed in writing. We reserve the right to change the stated data without prior notice. Paint may be regarded as a semi-finished product, and the final result depends on factors such as surface preparation, temperature, application method, type of substrate, etc.

Contact information

Gjøco AS
Ørvegen 1160, 6639 Torvikbukt
Telephone: +47 712 91 700
E-mail: office@gjoco.no

